

JOB NAME	
SALES REP	
ARCHITECT	
DESIGNER	
BUILDER	
INSTALLER	

COMMONWEALTH RECLAIMED PANELING COLLECTION

## Richmond



## STANDARD SPECIFICATIONS

APPLICATION Wall Paneling CONSTRUCTION Solid

LONSTRUCTION Solid

**WIDTHS** 3 1/2", 4 1/2" and 5 1/2"

LENGTHS Random 2' to 10'

THICKNESS 3/8" PROFILE Square

SPECIES Reclaimed Oak
SURFACE Original Surface
FINISH Unfinished

INTERNAL PRODUCT REFERENCE \_\_\_\_\_

Due to the organic nature of wood, variation in color, texture, and character will occur.

CHARACTER Mild Checking | Nail Holes | Some Knots | Saw Kerf | Color Variation | Mixed Grain

**APPLICATION** Walls | Box Beams | Doors

INSTALLATION Our flooring products should be installed following NWFA installation methods.

As a general guideline for wall board, we suggest that it is installed over plywood.

Installation methods vary greatly depending on site conditions and application. Please feel free to contact us to verify installation methods.

All products are fabricated to order with a lead time of 4 - 6 weeks. A shorter lead time may be available if the product is ordered within standard specifications and is in stock. Custom specifications such as wider widths, single widths, customized finishes, etc, are available by client request and may have an upcharge or extended lead time. Speak to your Trout River Reclaimed sales representative for more information and details.

