

JOB NAME _____
SALES REP _____
ARCHITECT _____
DESIGNER _____
BUILDER _____
INSTALLER _____

HERITAGE COLLECTION

Sandbridge

STANDARD SPECIFICATIONS

APPLICATION Flooring
CONSTRUCTION Engineered
CORE 12MM Baltic Birch Plywood
WEAR LAYER 4MM White Oak
THICKNESS 5/8"
LENGTHS Random 2' to 10'
FLOORING WIDTHS 5", 6" & 7"
EDGE PROFILE Tongue and Groove
END PROFILE End Matched T & G
EDGE Microbevel

SPECIES Character White Oak
SURFACE Smooth
FINISH Sandbridge, UV Oil Finish



INTERNAL PRODUCT REFERENCE _____


Due to the nature of reclaimed wood, variation in color, texture, and character will occur.

CHARACTER Mild Checking | Some Knots | Color Variation

APPLICATION Floors | Treads

INSTALLATION Our flooring products should be installed following NWFA installation methods. As a general guideline for wall board, we suggest that it is installed over plywood. Installation methods vary greatly depending on site conditions and application. Please feel free to contact us to verify installation methods.

All products are fabricated to order with a lead time of 2 - 4 weeks. A shorter lead time may be available if the product is ordered within standard specifications and is in stock. Custom specifications such as wider widths, single widths, customized finishes, etc, are available by client request and may have an upcharge or extended lead time. Speak to your Trout River Reclaimed sales representative for more information and details.



Trout River Reclaimed
(434) 645-2600
www.troutriverreclaimed.com